

UNS-LR A2 NIGHT VISION WEAPON SIGHT



SPECIFICATIONS

POWER SOURCE:	(1) AA OR 123 BATTERY	٨
BATTERY LIFE:	AA EXCEEDS 24 HRS, 123 EXCEEDS 36 HRS	F
CONTROLS:	PULL ON/OFF GAIN KNOB, FOCUS KNOB	В
MOUNT:	KAC MOUNT OR QUICK ATTACH/ DETACH TO MIL-STD-1913 RAIL OR EQUIVALENT	F V
RECOG. RANGE:	1000 M (HUMAN, 1/4 MOON)	S
FINISH:	FLAT BLACK MATTE OR DESERT	٧
	SAND BROWN, CORROSION RESISTANT	*P At

MAGNIFICATION:	UNITY	
FIELD OF VIEW:	9°	
BORE SIGHT:	WITHIN .5 MOA	
FOCUS RANGE:	20M TO INFINITY	
WATERPROOF:	3 FT. FOR 4 HRS	
SIZE:	9.6″L (244 MM)	
WEIGHT:	2.9 LBS. (1.31 KG)*	
*PRODUCT WEIGHTS MAY VARY DUE TO MANUFACTURING		

*PRODUCT WEIGHTS MAY VARY DUE TO MANUFACTURING AND CONFIGURATION PROCESSES.

FEATURES

- 》 1 YEAR WARRANTY
- SAIN CONTROL
- **CLIP-ON NIGHT VISION SCOPE**

- SIB[®]-SINGLE INTERCHANGE BATTERY
- W QUICK ATTACH/DETACH MOUNT
- WORKS WITH FRONT LINE LONG RANGE RIFLES

The Knight Vision[®] UNS-LR A2 clip-on Weapon Sight (WS) is a product improved version of the AN/PVS-30. The UNS-LR A2 adds the latest high performance Gen 3 light intensification night vision to most rifles and day scopes by attaching to the picatinny rail. This product is appropriate for front line long range rifles. When the UNS-LR A2 is added in front, your existing optic, eye relief, and cheek weld are undisturbed. Knight Vision patented Single Interchangeable Battery (SIB)[®] allows use of either CR123 or AA single cells, with a battery life exceeding 24 hours while the shooter remains in shooting position.



STANDARD ACCESSORIES

Operator's Manual, Soft Case, (1) AA Battery, Light Shroud and Lens Cleaning Kit.

Specifications subject to change without notice. Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State Office of Defense Trade Controls prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130. Approved for public release under International Traffic in Arms Regulations (ITAR) 22CFR 120.11